

RECEIVED
CENTRAL FAX CENTER

JUN 25 2009

In re Patent Application of:
TOWNSEND ET AL.
Serial No. 10/538,019
Filed: June 7, 2005

In the Claims:

Claims 1-10 (Cancelled).

11. (Currently Amended) A method of automated pallet repair, comprising the steps of:

using a scanning device to create a three-dimensional data map of a pallet for detecting gaps and protrusions in the pallet, the scanning device generating a laser beam projected onto the pallet;

filtering the three-dimensional data map into a two-dimensional image of on/off values by using a dynamically created height value, corresponding to a reference plane or set threshold offset above a board surface of the pallet;

creating a recipe of repair operations from the three-dimensional data map; and

gripping the pallet and transporting the gripped pallet to one or more repair stations in accordance with the recipe.

Claim 12 (Cancelled).

13. (Currently Amended) The method of claim 11 ~~claim 12~~, further comprising filtering the three-dimensional data map with a Sobel or Gaussian filter to provide locations of the gaps and protrusions in the pallet.

Claims 14-16 (Cancelled).

In re Patent Application of:
TOWNSEND ET AL.
Serial No. 10/538,019
Filed: **June 7, 2005**

17. (New) A method of automated pallet repair,
comprising the steps of:

using a scanning device to create a three-dimensional
data map of a pallet for detecting gaps and protrusions in the
pallet;

filtering the three-dimensional data map into a two-
dimensional image of on/off values by using a dynamically created
height value, corresponding to a reference plane or set threshold
offset above a board surface of the pallet;

creating a recipe of repair operations from the three-
dimensional data map; and

transporting the pallet to at least one repair station
in accordance with the recipe.

18. (New) The method of claim 17, further comprising
filtering the three-dimensional data map with a Sobel or Gaussian
filter to provide locations of the gaps and protrusions in the
pallet.

19. (New) The method of claim 17, wherein the scanning
device generates a laser beam projected onto the pallet.

20. (New) A method of automated pallet repair,
comprising the steps of:

generating a map of a pallet, the map including
features, dimensions and topography of the pallet;

In re Patent Application of:
TOWNSEND ET AL.
Serial No. 10/538,019
Filed: June 7, 2005

generating a recipe of repair operations based on the map; and

transporting the pallet to at least one repair station based on the recipe.

21. (New) The method of claim 20, wherein the map is generated using a scanning device, the scanning device generating a laser beam projected onto the pallet, and wherein the map comprises a three-dimensional data map.

22. (New) The method of claim 21, further comprising filtering the three-dimensional data map into a two-dimensional image.

23. (New) The method of claim 22, wherein the two-dimensional image comprises on/off values by using a dynamically created height value corresponding to a reference plane above a board surface of the pallet.

24. (New) The method of claim 22, wherein the two-dimensional image comprises on/off values by using a dynamically created height value corresponding to set threshold offset above a board surface of the pallet.

25. (New) The method of claim 21, further comprising filtering the three-dimensional data map with a Sobel or Gaussian filter to provide locations of gaps and protrusions in the pallet.

In re Patent Application of:
TOWNSEND ET AL.

Serial No. 10/538,019

Filed: June 7, 2005

26. (New) The method of claim 20, further comprising gripping the pallet before transporting the pallet to the at least one repair station.